

1. Unique identification of the product

MW 06 PRIMA

Index f

2. Product number

562071

3. Intended use of the product according to EN 14509

Internal and external wall

4. Manufacturer identification

 PANELCO SAS
 Route de Chaveyriat
 B.P. 10
 01540 Vonnas

5. Attestation of conformity system

3

6. The notified body

CSTB n°0679

realized reaction to fire tests and delivered the reaction to fire classification report

RA13-0084

7. Declared performance

Essential characteristics and performance			European Standard
Panel and faces	Thickness of panel	60 mm	EN 14509
	Thickness of external face	0.6 mm	
	Thickness of internal face	0.6 mm	
	Mass of the product	17.56 kg/m ²	
Steel	Tensile strength of external face	S320GD	
	Tensile strength of internal face	S320GD	
Core	Core	Mineral wool	
	Density of core material	130 kg/m ³	
Durability	Durability	Pass	
Mechanical resistance	Cross panel tensile strength	0.02 MPa	
	Shear strength	0.03 MPa	
	Shear modulus	3.2 MPa	
	Shear strength after long-term loading (100 000 h)	-	
	Compressive strength	0.05 MPa	
	Creap coefficient t= 2000 h	-	
	Creap coefficient t= 100 000 h	-	
	Wrinkling strength of the external face in span	77.6 MPa	
	Wrinkling strength of the external face in span - high temperature	58.5 MPa	
	Wrinkling strength of the external face over a central support	63.6 MPa	
	Wrinkling strength of the external face over a central support - high temperature	48.0 MPa	
	Wrinkling strength of the internal face in span	77.6 MPa	
	Wrinkling strength of the internal face over a central support	64.1 MPa	
Thermal insulation performance	Accessibility	-	
	Thermal conductivity of the core	0.041 W/(m.K)	
Fire	Thermal transmittance	0.623 W/(m ² .K)	
	Reaction to fire	A2-s1-d0	Report n° RA13-0084
Permeability	Fire resistance	NPD	EN 14509
	Air permeability	NPD	
	Water permeability	NPD	
Acoustic	Water vapour permeability	NPD	
	Airborne sound insulation	NPD	
Dimensional tolerances	Sound absorption	NPD	
	Dimensional tolerances	NPD	
Environnement	Substances of very high concern according to REACH	No	REACH
	Regulated hazardous substances emission	(a)	EN 14509

(a) Faces in contact with the interior air shall not emit regulated hazardous substances exceeding the maximum permitted levels specified in the European or national regulations. European test methods are being developed. An informative database of European and national provisions relating to controlled substances can be found on the EUROPA website, accessible at the following address:
https://ec.europa.eu/growth/tools-databases/cp-ds_en

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Vonnas, 05/09/2019

Mr. Philippe Calland

